Alpha-30R Mobile Barcode Printer

Empower Your Mobile Workforce Efficiency and Accuracy

The new generation TSC mobile printer, the Alpha-30R, is user-friendly and drop-resistant. It enhances customer service, boosts productivity and improves shopper experience in retail stores. The Alpha-30R is stylish and comfortable in use and prints receipts or labels on-demand. Mobile printing operations can be carried out much faster and with more accuracy.

The Alpha-30R is compact and very efficient, it also has a large capacity smart battery that enables it to carry out a full shift of work without interruption. The Apple-certified MFi Bluetooth® 5.0 connection and 802.11ac Wi-Fi fast roaming features allow the Alpha-30R to provide reliable and seamless communication with user devices to achieve optimal mobile field-work.

The Alpha-30R's smart battery paired with SOTI Connect and TSC Console remote printer management gives real-time visibility that helps enterprises scale their business activities seamlessly and efficiently.

The Alpha-30R design emphasizes durability, it has the most robust specifications in its class. The ruggedness of the Alpha-30R meets MIL-STD-810 military-grade standards for drop and vehicle vibrations. It has an IP54 rating and will withstand a 2.1 m drop and a 1.0 m tumble. While the protective case allows it to withstand a 2.5 m drop in a harsh environment.

The Alpha-30R has a full line of accessories to meet a range of different environments on the go. It is especially suited for retail applications. It is also environmentally friendly and can support linerless media printing to reduce waste. Go green!

Key Features



Sophisticated TSC Sense Care

- Auto scans and detects printhead bad dots during printing
- Monitors the smart battery to ensure full-shift productivity, reduces total cost of ownership and avoids downtime



Dynamic Remote Printer Management

 SOTI Connect and TSC Console support multiple management tasks. This reduces costs and avoids downtime of businesscritical devices



- MFi Bluetooth[®] 5.0 with NFC tap-topair setup enables easy connectivity
- Dual-band Wi-Fi with fast roaming as well as enterprise-grade security ensures reliable and safe operation



- IP54 rating for dust and water resistance
- Rugged design for drops from 2.1 m and tumbles from 1.0 m



Full Line of Accessories

- Assist in performing diverse labeling tasks including hands-free mobility
- Fulfills linerless printing needs



- Software Pack
- Supports label printing applications for different platforms
- TSC mobile printing app is available for both iOS and Android[™] users

Applications



Retail

- Chain stores shelf labeling
- Super market relabeling



Healthcare

- Mobile specimen collection
- Drug management
- Asset label



Transportation and Logistics

- Shipping and receiving
- · Direct store delivery



Manufacturing

- Raw materials, finished goods
 - Asset management



Mobile Printing For Your Business

Key Benefits



Faster and Rugged Design for On the Go Printing

The innovatively designed Alpha-30R features two models with different print speeds. The basic model offers up to 5 ips, while the premium model goes up to 6 ips to enhance field worker productivity. They are built for durability, and the Alpha-30R is IP54 rated for dust and water resistance. It has been rigorously tested to withstand a 2.1 m drop and an 800 drops tumble. When used with a protective case, the ruggedness level is improved and the printer will withstand a 2.5 m drop. The Alpha-30R meets MIL-STD-810 military standards for drop and vehicle vibration as proof of the rugged design for all your field mobility solutions.



Easy Remote Printer Management with SOTI Connect and TSC Console

Quickly and remotely monitor a fleet of Alpha-30R mobile printers, configure settings, deploy programs, and troubleshoot problems using SOTI Connect and TSC Console's powerful printer management tools to avoid downtime and lower the total cost of ownership. The Alpha-30R's smart battery, paired with printer management tools, can intelligently monitor battery health status and remaining capacity to ensure continuous productivity over a full shift.



Seamless Mobility Communication

Seamless and reliable wireless connectivity is crucial for mobile devices. TSC has introduced our latest 802.11 a/b/g/n/ac Wi-Fi certified module which enables fast roaming and enterprise-grade security to ensure reliable and safe operation. The Alpha-30R is equipped with Apple-certified MFi Bluetooth® 5.0 with NFC tap-to-pair for easy connectivity, and users get a secure connection to print labels on-demand. The TSC Mobile Utility APP is available for both iOS and Android™ users. This APP makes it easy for authorized IT staff to troubleshoot and solve mobile printer problems quickly and efficiently.



Full Line of Accessories

The Alpha-30R offers a full line of accessories including a protective case, multiple battery charging options and more to meet your receipt and label printing requirements. Available with a complete forklift and vehicle accessory option, the Alpha-30R's vehicle mount adaptor gives users the flexibility to easily integrate the printer with a forklift with intuitive RAM[®] mount components.



Integrated Software Pack

The Alpha-30R supports OPOS drivers and provides mainstream platform SDK including Windows[™], Windows[™] Mobile (WinCE), Android[™], and iOS. The OPOS and SDK software packs integrated into the Alpha-30R mobile printer allow users to interpret ESC/POS commands and to develop applications compatible with the unified POS specification. After integration, the customized software can be leveraged and tailored to switch between POS terminals and printers for quick port communications, connections, and print command transfers.

Alpha-30R Accessories

| Alpha-30R | Description | Factory Option | User Option |
|--|---|-------------------|----------------|
| | Protective Case with Shoulder Strap The protective case enhances the extra level of protection for harsh environment especially for the outdoor usage. | | ~ |
| | Shoulder Strap Designed for carrying the printer directly without a protective case. | | ~ |
| | Belt Clip Use the belt clip for a complete hands-free solution. | | ~ |
| | Li-ion Smart Battery The Li-on smart battery works with TSC Console and SOTI Connect to monitor battery information, charge cycles, and remaining capacity. | | ~ |
| 2 27 2 | 1-Slot Docking Cradle Easily charge the printer without removing the battery. | | ~ |
| | 4-Slot Docking Cradle Easily charge multiple printers without removing the battery. | | ~ |
| The second se | 1-Slot Battery Charger Use the 1-slot charger to quickly charge the battery without any downtime. | | ~ |
| and a second sec | 4-Slot Battery Charger The 4-slot charger is well-suited for heavy-duty missions. | | ~ |
| | 12-24VDC Vehicle Power Adaptor For automobile vehicle plug to charge on the car. | | ~ |
| | 12-60VDC Vehicle Power Adaptor For automobile vehicle plug to charge on the car. | | ~ |
| | Battery Eliminator Connect printer and vehicle power source directly by open-ended wire without using battery. It can be used with vehicle mount adaptor. | | ~ |
| | Vehicle Mount Adaptor Easily mount the printer on a forklift. | | ~ |
| | Linerless Kit The linerless kit suits linerless printing needs. | ~ | |

Alpha-30R | Data Sheet

| Printer model | Alpha | | |
|----------------------------|---|--|--|
| Version | Basic | Premium | |
| Resolution | 8 dots/mm (203dpi) | | |
| Printing method | Direct Thermal | | |
| Max. print speed | Up to 127 mm (5″)/second | Up to 152 mm (6″)/second | |
| Max. print width | 72 mm | (2.83") | |
| Max. print length | 2,794 mm (110") | | |
| Enclosure | Plastic with rubber over molded | | |
| Physical dimension | 118 mm (W) x 158 mm (H) x 68 mm (D) 4.64" (W) x 6.22" (H) x 2.68" (D) | | |
| Weight (including battery) |) 0.65 kg (1.43 lbs) | | |
| Drop specification | 2.1 m (6.9 ft), with protective case can be 2.5 m (8.2 ft) | | |
| MIL-STD 810 | Drop and vibration | | |
| Tumble test | 800 free falls from 1 m (3.3 ft), with protective case can be 1000 free falls from 1 m (3.3 ft) | | |
| IP rating | IP54 (w/o case, paper path is excluded) | | |
| Max. roll capacity | 57 mm (2.24") 0D | | |
| Processor | 32-bit RISC CPU | | |
| Memory | 128 MB SDRAM, 128 MB Flash | | |
| Interface | Either one selected | | |
| | Type C USB 2.0 + MFi Bluetooth 5.0 + Passive NFC tag Type C USB 2.0 + 86 Bluetooth 4.2 + Passive NFC tag Type C is for communication only | | |
| Power | 7.4V DC, 3080 mAh Li-ion rechargeable battery | 7.4V DC, 3030 mAh Li-ion rechargeable smart battery | |
| Operation switch, button | 3 buttons (On/off, feed, and cover-open) 2 color LEDs for printer status and battery charging status 1 LCD for printer status | | |
| Sensors | Reflective sensor Head open sensor | • Reflective sensor • Gap sensor • Head open sensor | |
| Real time clock | Standard | | |
| Internal fonts | 8 alpha-numeric bitmap fonts One Monotype Imaging® CG Triumvirate Bold Condensed scalable font | | |
| Bar code | 1D bar code Code 39, Code 93, Code128UCC, Code128 subsets A.B.C, Codabar, Interleave 2 of 5, EAN-8, EAN-13, EAN-128, UPC-4, UPC-E, EAN and UPC 2(5) digits add-on, MSI, PLESSEY, POSTNET, China POST, GS1 Data bar 2D bar code PDF-417, Maxicode, DataMatrix, QR code, Aztec | | |
| Printer language | TSPL-EZC (EPL2, ZPL2, CPCL), or ESC-POS | | |
| Media type | Receipt paper, receipt paper with black mark in printing side, selected label, linerless (outside wound) | Receipt paper, receipt paper with black mark in printing side or backside, label, linerless (outside wound) | |
| Media width | 25.4 ~ 80 mm (1' | " ~ 3.15" w/ liner) | |
| Media thickness | 0.06 ~ 0.16 mm (2.36 ~ 6.3 mil) | | |
| Media height | | | |
| Media core diameter | Label: Min. 25.4 mm (1") Standard: 12.7 mm (0.5") Optional: 19.05 mm (0.75") | | |
| Environment condition | Operation: -20 ~ 55°C (-4 ~ 131 °F), 10 ~ 90% non-condensing Storage: -30 ~ 70°C (-22 ~ 158 °F), 10 ~ 90% non-condensing | | |
| Environmental concern | Comply with RoHS, WEEE | | |
| Accessories | Ouick start guide Ouick start guide Belt Clip Li-ion battery Power adapter | | |
| Limited warranty | Printer: 2 years Print head: 25 km (1 million inches) or 12 months which comes first Platen: 50 km (2 million inches) or 12 months which comes first Battery: 1 year | | |
| Factory options | Linerless kit | | |
| User options | Type C USB 2.0 cable 0.75" media core adaptor Protective case with shoulder strap Shoulder strap 1-slot docking cradle 4-slot docking cradle | 4-slot battery charger 12-24VDC vehicle power adaptor 12-60VDC vehicle power adaptor 12-48VDC power source with battery eliminator Vehicle mount adapter can be used | |













CORPORATE HEADQUARTERS

TSC Auto ID Technology Co., Ltd. Tel: +886 2 2218 6789 E-mail: apac_sales@tscprinters.com

LI ZE PLANT

TSC Auto ID Technology Co., Ltd. Tel: +886 3 990 6677 E-mail: apac_sales@tscprinters.com

AMERICAS

TSC Auto ID Technology America Inc. Tel: +1 657 258 0808 E-mail: americas_sales@tscprinters.com

MEXICO

TSC Mexico Representative Office Tel: +1 52 (33) 3673 1406 E-mail: americas_sales@tscprinters.com

BRAZIL

TSC Brazil Representative Office Tel: +55 (11) 3554 7225 E-mail: americas_sales@tscprinters.com

EMEA

TSC Auto ID Technology EMEA GmbH Tel: +49 (0) 8106 37979 000 E-mail: emea_sales@tscprinters.com

RUSSIA

TSC Auto ID Technology EMEA GmbH Tel: +7 495 249 9017 E-mail: emea_sales@tscprinters.com

Middle East

TSC Auto ID Technology ME Ltd, FZE Tel: +971 4 2533 069 E-mail: emea_sales@tscprinters.com

ASIA PACIFIC

TSC Auto ID Technology Co., Ltd. Tel: +886 2 2218 6789 E-mail: apac_sales@tscprinters.com

INDIA

TSC India Distributor's Office Tel: +91 2267 082 465 E-mail: apac_sales@tscprinters.com

CHINA

Tianjin TSC Auto ID Technology Co., Ltd. Tel: +86 22 5981 6661 E-mail: apac_sales@tscprinters.com

KOREA

TSC Korea Representative Office Tel: +82 2 852 3322 E-mail: apac_sales@tscprinters.com

TSC PRINTRONIX

TSC Printronix Auto ID tscprinters.com

TSC® is a trademark of TSC Auto ID Technology Co., Ltd. TSC Auto ID Technology Co., Ltd. is an ISO 9001/14001 registered company. © 2022 TSC Auto ID Technology Co., Ltd. V0522